

COGGED V - GUIDES FOR FABRICATED VOLTA FLAT BELTS

Suitable to Volta Flat Belt Types: L, LW, LB, W, M, MW, MB, MB-LT, Z, GZ, G

GUIDE TYPE	DIMENSIONS W x H		WEIGHT		ADDITIONAL MPD	
	Inch x Inch	mm x mm	lbs/ft	kg/m	inch	mm
<u>90A Shore Hardness</u> CM-10/Z	$\frac{3}{8} \times \frac{15}{64}$	10 x 6	0.035	0.05	2	50
CM-13/A	$\frac{1}{2} \times \frac{5}{16}$	13 x 8	0.06	0.09	2.36	60
CM-17/B	$\frac{5}{8} \times \frac{7}{16}$	17 x 11.5	0.10	0.15	3.35	85
CM-22/C	$\frac{7}{8} \times \frac{35}{64}$	22 x 14.5	0.16	0.25	4.3	110
<u>80A Shore Hardness</u> CL /CLC/CLB-10/Z	$\frac{3}{8} \times \frac{15}{64}$	10 x 6	0.035	0.05	1.4	35
CL /CLC/CLB-13/A	$\frac{1}{2} \times \frac{5}{16}$	13 x 8	0.06	0.09	1.6	40
CL /CLC/CLB-17/B	$\frac{5}{8} \times \frac{7}{16}$	17 x 11.5	0.10	0.15	2.36	60
<u>80A LT Shore Hardness</u> CLC-LT/CLB-LT-10	$\frac{3}{8} \times \frac{15}{64}$	10 x 6	0.035	0.05	1.2	30
CLC-LT-13	$\frac{1}{2} \times \frac{5}{16}$	13 x 8	0.06	0.09	1.4	35
<u>75A LT Shore Hardness</u> CFB-10	$\frac{3}{8} \times \frac{15}{64}$	10 x 6	0.035	0.05	1.05	27
CFB-13	$\frac{1}{2} \times \frac{5}{16}$	13 x 8	0.06	0.09	1.30	33
CFC/CFB-17	$\frac{5}{8} \times \frac{7}{16}$	17 x 11.5	0.10	0.15	1.75	45
<u>65A Shore Hardness</u> CSB-8	$\frac{5}{16} \times \frac{13}{64}$	8 x 5	0.027	0.04	0.79	20
CSC/CSB-10	$\frac{3}{8} \times \frac{15}{64}$	10 x 6	0.035	0.05	0.85	22
CSC /CSB-13	$\frac{1}{2} \times \frac{5}{16}$	13 x 8	0.06	0.09	1.1	28
CSC /CSB-17	$\frac{5}{8} \times \frac{7}{16}$	17 x 11.5	0.10	0.15	1.4	40

All Values are nominal and to the best of our experience are true and accurate.