



FELB ITP Flat, Solid, Embossed Bottom, Fine Points Texture Top Belt

Material:	Volta LB
Color (for inspiration only):	Blue02
Hardness:	80A
Standard Belt Width:	60" / 1524mm
Temp. Range:	- 40°C to 50°C / -40°F to 120°F
Certification:	FDA /EU

Coefficient of friction Embossed Bottom:	
Steel	0.45

Belt TYPE		FELB-2-ITP	
			
Thickness	mm	2	
Weight	kg/m ²	1.699	
	lb/ft ²	0.349	
Minimum Pulley:	mm	12	
	Inch	1/2	
Maximum Work Load	Kg/cm	2	
	lb/inch	11.2	
Pull Force (kg/cm) at pretension of:	0.5%	0.2	
	1%	0.4	
	1.5%	0.6	
	2%	0.8	
	2.5%	1.0	
	3%	1.2	
Pull Force (lb/in) at pretension of:	0.5%	1.12	
	1%	2.24	
	1.5%	3.36	
	2%	4.48	
	2.5%	5.6	
	3%	6.72	
Electrode Splicing	EVLB 7	✓	
	EVLB 9	✓	

Notes:

1. Pull force relates to steel pulleys. Multiply given values by 0.9 for cast iron, 1.1 for rubber and 0.8 for wet smooth drums.
2. All values are nominal and to the best of our experience are true and accurate.
3. English dimensions have been converted from metric measurements