



**VOLTA FELB MC** Flat Mini Cleat, Solid, Embossed Bottom Belt

Material:	<b>Volta LB, Blue</b>
Hardness:	80A
Standard Belt Width:	60" / 1524mm
Temp. Range:	- 40°C to 50°C / -40°F to 120°F
Certification:	FDA/EU

Coefficient of friction (Steel):	
Belt Embossed Bottom:	0.45

TYPE		FELB-2.5 MC	
			
Thickness	mm (h//H)	2.5//5.3	
Weight	kg/m <sup>2</sup>	3.6	
	lb/ft <sup>2</sup>	0.71	
Minimum Pulley:	Normal	mm	40
	Flex:	Inch	1 5/8
	Back	mm	35
	Flex:	Inch	1 5/8
Maximum Work Load	Kg/cm	2.5	
	lb/inch	14	
Pull Force (kg/cm) at pretension of:	0.5%	0.25	
	1%	0.50	
	1.5%	0.75	
	2%	1.0	
	2.5%	1.25	
	3%	1.50	
Pull Force (lb/in) at pretension of:	0.5%	1.4	
	1%	2.8	
	1.5%	4.2	
	2%	5.6	
	2.5%	7.0	
	3%	8.4	
Electrode Splicing	EVLB 7	✓	
	EVLB 9	✓	

**Notes:**

1. Pull force relates to steel pulleys. Multiply given values by 0.9 for cast iron, 1.1 for rubber and 0.8 for wet smooth drums.
2. English dimensions have been converted from metric measurements.
3. All values are nominal and to the best of our experience are true and accurate.