

FEL ITR 10 Flat, Solid Embossed, Impression Top

Material:	Volta L, Brown
Hardness:	80A
Standard Belt Width:	60" / 1524mm
Temp. Range:	-40°C to 50°C / -40°F to 120°F
Certification:	FDA

Coefficient of friction (Steel):	
Embossed Bottom Surface:	0.45

Type		FEL-4 ITR 10
		
Thickness	inch	0.16
	mm	4
Weight	lb/ft ²	0.76
	kg/m ²	3.8
Min. Pulley Diameter	inch	1
	mm	25
Maximum Work Load	lb/inch	5.0
	kg/cm	3.5
Pull Force (lb/in) at pretension of:	0.5%	1.74
	1.0%	3.47
	1.5%	5.2
	2.0%	6.94
Pull Force (kg/cm) at pretension of:	0.5%	0.31
	1.0%	0.62
	1.5%	0.93
	2.0%	1.24
Electrode Splicing	EVL 7	-
	EVL 9	✓

Notes: 1. Pull Force in table relates to steel pulleys. Multiply given values by 0.9 for cast iron, 1.1 for rubber and 0.8 for wet smooth drums.
 2. English dimensions have been converted from metric measurements.
 3. All values are nominal and to the best of our experience are true and accurate.