

V - GUIDES FOR FABRICATED VOLTA FLAT BELTS

For Volta FHW, FHB and FK:

GUIDE TYPE	DIMENSIONS W x H		WEIGHT		ADDITIONAL MPD	
	inch x inch	mm x mm	Lbs/ft	kg/m	inch	mm
VW / VWB - 10/Z	$\frac{3}{8} \times \frac{15}{64}$	10 x 6	0.04	0.06	2.75	70
VW / VWB - 13/A	$\frac{1}{2} \times \frac{5}{16}$	13 x 8	0.07	0.10	3.15	80
VW / VWB - 17/B	$\frac{5}{8} \times \frac{7}{16}$	17 x 11.5	0.12	0.18	4.3	110
VW / VWB - 22/C	$\frac{7}{8} \times \frac{35}{64}$	22 x 14.5	0.19	0.29	6.0	150
CW / CWB - 10/Z	$\frac{3}{8} \times \frac{15}{64}$	10 x 6	0.035	0.05	2.15	55
CW / CWB - 13/A ¹	$\frac{1}{2} \times \frac{5}{16}$	13 x 8	0.06	0.09	2.35	60
CW / CWB - 17/B ²	$\frac{5}{8} \times \frac{7}{16}$	17 x 11.5	0.10	0.15	3.35	85
CW / CWB - 22/C ³	$\frac{7}{8} \times \frac{35}{64}$	22 x 14.5	0.16	0.25	4.34	110

- Notes:**
1. Recommended Guide Profiles for up to 2.5 mm thick Flat Belts.
 2. Recommended Guide Profiles for 2.5 to 4.5 mm thick Flat Belts.
 3. Recommended Guide Profiles for Flat Belts Thicker than 4.5 mm.

All Values are nominal and to the best of our experience are true and accurate