


RMW Round Reinforced Profile

Material:	Volta MW, beige
Hardness:	95A / 46D
Temp. Range:	-20 °F to +140 °F
Certifications:	FDA/USDA/EU

Coefficient of friction :	
Steel:	0.36
Aluminum:	0.36
UHMW:	0.30



RMW

BELT TYPE	DIAMETER ∅ inch	WEIGHT lb / ft	MIN. PULLEY ∅ inch	MAX. LOAD lb	PULLFORCE (lb) AT PRETENSION			DRILL BIT
					0.5 %	1%	1.5%	
RMW-6.3	1/4	0.025	3	60	22	44	NR	I
RMW-8	5/16	0.04	3 3/4	93	39	77	NR	I
RMW-9.5	3/8	0.06	4 3/8	139	40	81	121	I
RMW-12.5	1/2	0.10	6	232	62	125	187	II
RMW-15	5/8	0.14	7	337	66	132	198	II
RMW-18	23/32	0.20	8 3/8	474	71	141	212	III

Notes:

1. Pull Force in tables relate to grooved steel and aluminum grooved pulleys. Multiply given values by 0.7 for wet pulleys.
2. Dimensions have been converted from metric measurements.
3. All values are nominal and to the best of our experience are true and accurate.
4. NR = Not Recommended.