

## SOLID V - GUIDES FOR FABRICATED VOLTA 'H' MATERIAL FLAT BELTS

Suitable for Volta Flat Belt Types: **FHB, FHW,FW & FK**

GUIDE TYPE	DIMENSIONS W x H		WEIGHT		ADDITIONAL MPD	
	Inch x Inch	mm x mm	lbs/ft	kg/m	inch	mm
<i>40D Shore Hardness</i>						
<b>VW -8 /M</b>	$\frac{5}{16} \times \frac{13}{64}$	8 x 5.2	0.01	0.047	2.36	60
<b>VW – 10/Z</b>	$\frac{3}{8} \times \frac{15}{64}$	10 x 6	0.04	0.06	2.75	70
<b>VW / VWB – 13/A</b>	$\frac{1}{2} \times \frac{5}{16}$	13 x 8	0.07	0.10	3.15	80
<b>VW / VWB – 17/B</b>	$\frac{5}{8} \times \frac{7}{16}$	17 x 11.5	0.12	0.18	4.3	110
<b>VW – 22/C</b>	$\frac{7}{8} \times \frac{35}{64}$	22 x 14.5	0.19	0.29	6.0	150
<i>40D Shore Hardness</i>						
<b>CW– 10/Z</b>	$\frac{3}{8} \times \frac{15}{64}$	10 x 6	0.035	0.05	2.15	55
<b>CW– 13/A<sup>1</sup></b>	$\frac{1}{2} \times \frac{5}{16}$	13 x 8	0.06	0.09	2.35	60
<b>CW– 17/B<sup>2</sup></b>	$\frac{5}{8} \times \frac{7}{16}$	17 x 11.5	0.10	0.15	3.35	85
<b>CW– 22/C<sup>3</sup></b>	$\frac{7}{8} \times \frac{35}{64}$	22 x 14.5	0.16	0.25	4.34	110

- Notes: 1. Recommended Guide Profiles for up to 2.5mm thick Flat Belts.  
 2. Recommended Guide Profiles for 2.5 to 4.5mm thick Flat Belts.  
 3. Recommended Guide Profiles for Flat Belts thicker than 4.5mm.

All Values are nominal and to the best of our experience are true and accurate.