


VPF-RT

Ridge-Top Solid Profile

Material:	Volta PF, Beige
Hardness:	88 A / 37 D
Temp. Range:	-30° C to +60° C
Certifications:	FDA/EU

Coefficient of friction :	
Steel:	0.38
Aluminum:	0.38



VPF-RT

BELT TYPE	DIMENSIONS W x H mm X mm	WEIGHT kg/m	MIN. PULLEY Ø mm	MAX. WORK LOAD kg	PULL FORCE (kg) AT PRETENSION		
					1 %	2 %	3 %
VPF-C-RT	22 x 24.5	0.43	235	90	14.3	28.6	42.9

Notes:


1. Pull Force in tables relate to Steel and Aluminum pulleys. Multiply given values by 0.9 for Cast Iron and 0.8 for wet pulleys.
2. All values are nominal and to the best of our experience are true and accurate.

VPF-RT

Ridge-Top Solid Profile

Material:	Volta PF, Beige
Hardness:	88 A / 37 D
Temp. Range:	-20° F to +140° F
Certifications:	FDA/EU

Coefficient of friction :	
Steel:	0.38
Aluminum:	0.38



VPF-RT

BELT TYPE	DIMENSIONS W x H inch X inch	WEIGHT lbs/ft	MIN. PULLEY Ø inch	MAX. WORK LOAD kg	PULL FORCE (lbs) AT PRETENSION		
					1 %	2 %	3 %
VPF-C-RT	7/8 x 31/32	0.29	9 1/4	198	31.5	63	94.5

Notes:

1. Pull Force in tables relate to Steel and Aluminum pulleys. Multiply given values by 0.9 for Cast Iron and 0.8 for wet pulleys.
2. All values are nominal and to the best of our experience are true and accurate.